



REM-IND-C

CONVENTIONAL VISUAL
INDICATING DEVICE - VID

REMOTE INDICATOR

Ripetitore LED



The GFE-REM-IND-C conventional flashing remote with visual indication device can be used with any fire alarm detector, be it of the conventional types, to indicate remotely the activation of the relevant detection device.

Its main characteristics are the high visibility due to the flashing of 2 high efficiency LEDs and the wide operating voltage range (3.3V to 10V DC) with a maximum 7mA current consumption. The connections of this device are non-polarised.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	3.3V to 10V DC
SUPPLY CURRENT	7mA max.
MAX. CABLE SIZE	2.5 mm ²
MATERIAL	ABS
COLOUR	White or Black
IP RATING	IP40
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	-10°C to 50°C
DIMENSIONS	86 (L) x 86 (W) x 25 (H) mm
WEIGHT	50.1g = module 4,8g + box 45,3g

ORDER CODE

REM-IND-C - Codice articolo FSP SISTEMI: 3200-RL

CONVENTIONAL VISUAL INDICATING DEVICE

www.fspsystemi.it

