



EN54-3 Type A
CERTIFIED
1328-CPR-0287



► VALKYRIE CS

Conventional Wall Mount Sounder/ Beacon

Available in 2 colours

The **VALKYRIE CS** is a wall mounted Conventional Sounder/ Beacon with low power consumption. **Four different tones** are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS	VALKYRIE CS
SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 30 V DC
CURRENT - BEACON ACTIVE	1.4 mA
SOUNDER OUTPUT - CONTINUOUS	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
SOUNDER OUTPUT - LOW FREQ.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
SOUNDER OUTPUT - HIGH FREQ.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
MAX. CABLE SIZE	2.5 mm ²
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	-10°C to 55°C
COLOUR / CASE MATERIAL	Red or White / ABS
PROTECTION CATEGORY	IP21C - Type A - Indoor use
DIMENSIONS	110 (D) x 85 (H) mm inc. base
WEIGHT	254 g - including mounting base
ORDER CODE	DESCRIPTION
VALKYRIE CS	VALKYRIE CONVENTIONAL WALL SOUNDER
VALKYRIE CSB	VALKYRIE CONVENTIONAL WALL SOUNDER/ BEACON